



**EUR 3**

***CENTRALIZED LUBRICATION  
SYSTEM***



**OPERATION AND MAINTENANCE MANUAL**

## Index

<b>PART 1 – GENERAL CONSIDERATIONS.....</b>	<b>4</b>
<b>OVERVIEW OF THE COMPANY .....</b>	<b>4</b>
<b>MANUFACTURER'S DATA.....</b>	<b>4</b>
<b>CUSTOMER SERVICE .....</b>	<b>4</b>
<b>GENERAL WARNINGS.....</b>	<b>5</b>
<b>SYMBOL LEGEND .....</b>	<b>5</b>
<b>SCOPE OF THIS MANUAL .....</b>	<b>5</b>
<b>HANDBOOK STRUCTURE .....</b>	<b>6</b>
<b>SAFETY STANDARDS APPLIED.....</b>	<b>6</b>
<b>DECLARATION OF CONFORMITY .....</b>	<b>7</b>
<b>1.1.0) RECOMMENDED USE.....</b>	<b>8</b>
<b>1.2.0) SAFETY .....</b>	<b>9</b>
<b>1.3.0) DESCRIPTION OF THE SYSTEM.....</b>	<b>9</b>
<b>1.4.0) TECHNICAL SPECIFICATIONS .....</b>	<b>10</b>
1.4.1) ELECTROPUMP .....	10
1.4.2) PUMPING ELEMENT .....	14
• SIGNALING VALVE (with recirculation of grease).....	16
• SIGNALING VALVE (with ejection grease) .....	16
• MANOMETER .....	17
1.4.3) PIPES.....	18
• MAIN PIPE.....	18
• SECONDARY PIPE.....	19
1.4.4) DISPENSER .....	19
• DOUBLING OF FLOW RATE .....	25
• BRIDGE OUTPUT CONNECTION .....	26
• INDICATOR PULSE OF VISUAL INSPECTION .....	26
1.4.5) FITTINGS.....	26
• RECYCLABLE FITTING .....	27
• QUICK FITTING .....	28
• EXTENSIONS.....	29
1.4.6) TIMER.....	30
• PAUSE/WORKING CYCLE.....	31
• PAUSE/SENSOR WORKING CYCLE .....	31
1.4.7) SENSOR CONTROL WORKING DISTRIBUTORS.....	31
• SENSOR CODE 095032 FOR AUTOMOTIVE APPLICATIONS.....	31
• SENSOR CODE 095010 FOR INDUSTRY APPLICATIONS .....	32
1.4.8) MINIMUM LEVEL .....	33

<b>1.5.0) STORAGE.....</b>	<b>34</b>
<b>1.6.0) ASSEMBLY .....</b>	<b>34</b>
1.6.1) OPERATING PROCEDURE.....	35
• ELECTROPUMP .....	36
• PUMPING ELEMENT.....	37
• FITTINGS .....	37
• DISPENSER.....	38
• SENSOR.....	38
• MAIN AND SECONDARY PIPES.....	38
• ELECTRICAL CONNECTION 12/24 V DC.....	39
• VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK .....	39
• VERSION WITH TIMER PAUSE/SENSOR.....	39
• VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK AND MINIMUM LEVEL....	40
• VERSION with TIMER PAUSE/SENSOR and MINIMUm LeVEL .....	40
• electrical connection 110/220 V AC .....	41
• VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK .....	41
• VERSION WITH TIMER PAUSE/SENSOR .....	42
• VERSION without TIMER Or with TIMER PAUSE/work and MINIMUm LeVEL .....	42
• VERSION with TIMER PAUSE/SENSOR and MINIMUm LeVEL .....	43
• remote control device.....	43
1.6.2) WIRING DIAGRAM VERSION 12/24 V DC.....	44
▪ VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK.....	44
▪ VERSION WITH TIMER PAUSE/SENSOR .....	44
1.6.3) WIRING DIAGRAM VERSION 110/-220 V DC.....	45
▪ VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK.....	45
▪ VERSION WITH TIMER PAUSE/SENSOR .....	46
<b>PART 2 – OPERATING MANUAL .....</b>	<b>47</b>
<b>2.1.0) COMANDS .....</b>	<b>47</b>
<b>2.2.0) TIMER PROGRAMMING .....</b>	<b>48</b>
<b>2.3.0) TANK FILLING.....</b>	<b>51</b>
2.3.1) LUBRIFICANTS .....	51
<b>2.4.0) START-UP .....</b>	<b>52</b>
2.4.1) OPERATING PROCEDURE.....	52
<b>PART 3 – MAINTENANCE INSTRUCTION.....</b>	<b>53</b>
<b>3.1.0) MAINTENANCE INSTRUCTION .....</b>	<b>53</b>

---

<b>3.2.0) SCHEDULED MAINTENANCE.....</b>	<b>53</b>
<b>3.3.0) ANOMALIES .....</b>	<b>54</b>
<b>PART 4 – SPARE PARTS .....</b>	<b>56</b>

## *PART 1 – GENERAL CONSIDERATIONS*

### *OVERVIEW OF THE COMPANY*

**CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** is specialized in the design, manufacture and installation of centralized lubrication points. The company, which initially produced industrial vehicles only, has developed in the years, thanks to the vast experience acquired, earth moving machines and machinery for industrial applications.

Its dynamism has led it to upgrade its engineering, manufacturing and quality control systems with state-of-the-art solutions.

The Quality Control System adopted by the company was certified, in 2001, as compliant with the requirements of standard UNI EN ISO 9002 by the certification body named Det Norske Veritas Italia s.r.l..

The company's mission is supply its customers with a full assistance, from the supply, installation of dependable products down to on-site maintenance.

**CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.**, is a leading Italian company, with over 35 years of experience that has gradually expanded its market and now serves several European customers.

### *MANUFACTURER'S DATA*

Name	- <b>CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.</b>
Address	- Via Vittorio Alfieri, 10 – San Miniato Basso 56028 – Pisa ITALIA
Telephone	- +39 0571 42661
Fax	- +39 0571 42244
Web site	- <a href="http://www.ciaponi.it">www.ciaponi.it</a>
E-mail address	- <a href="mailto:info@ciaponi.it">info@ciaponi.it</a>
Tax-payer code/VAT no.	- IT01160480503

### *CUSTOMER SERVICE*

**CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** follows its customer directly by means of its post-sale servicing.

To request further information or order spare parts, it is possible to contact the **Customer Service** at the phone/fax numbers listed above.

## GENERAL WARNINGS

© All rights reserved. Fourth edition, July 2013.

This Maintenance and Operation Manual has been prepared by **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** and is supplied as is.

Therefore, it cannot be copied, reproduced, circulated or transcribed, in whole or in part, without the written authorization of **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.**.

The Manufacturer may change the content of this manual at any time, without warning, for technical or commercial reasons or to comply with new standards or laws.

### SYMBOL LEGEND

#### Key to symbols for the correct text interpretation

The symbols listed will be reported to the left of the text or in the vicinity of contents to which the reader should pay attention.

 Prohibition signal: it prohibits an action that could cause a hazard.

 Prescription signal: it prescribes specific behavior.

 Warning signal: it warns of a risk or generic danger.

 Electrical warning signal: it warns of a risk or danger of contact with electrical parts.

 Education signal: it feels you follow the instructions on the side.

### SCOPE OF THIS MANUAL

This manual supplies the user with all the information required to install, use, service and dismantle the system.

**CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** shall not be responsible for damages or faults caused by the failure to comply with the warnings and instructions provided below.

It is therefore advisable to:

- Carefully read all the parts of the Operation and Maintenance Manual.
- Keep a copy of the manual in a safe place and always make it available to all operators working with it.

## HANDBOOK STRUCTURE

The Complete Handbook is composed of the following parts.

### Part 1 – General aspect

Consists of all the information of product presentation, describing the purpose and scope, the technical characteristics of the main components and the different versions, as well as the directions for the correct installation of centralized lubrication.

### Part 2 – User Manual

Consists of all the general information is the entire set of information necessary for the operation of the plant and for correct control and use of the same.

### Part 3 – Instruction for maintenance

Consists of all the information needed to adequately perform some simple maintenance. In this part there are also some very useful information in the event of a malfunction.

### Part 4 – Spare parts

Consists of all the information necessary for the management of spare parts.

## SAFETY STANDARDS APPLIED

Centralized lubrication systems are designed, manufactured and installed in accordance with the requirements set forth in Directive 2006/42/EC. Therefore, for the purposes of the EC marking implant, that is placed in the position shown in Figure 1, adhesive is applied to a metal plate, as shown in figure 2, and in which are contained the following information:



Figura 2

Manufacturer's data

- Model / Type
- Serial number / Year of manufacture



Figura 1

- Power supply data

Example of a metal plate for EC marking of a pump model Euro 3, type 150302, power supply 24 V DC, serial number 038646 and lot of construction 11/06 (month / year).

**DECLARATION OF CONFORMITY**

The Manufacturer - **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.**

Address - Via Vittorio Alfieri, 10  
San Miniato Basso - 56028 PISA  
ITALIA

Telephone - +39 0571 42661

Fax - +39 0571 42244

Website - [www.ciaponi.it](http://www.ciaponi.it)

E-mail address - [info@ciaponi.it](mailto:info@ciaponi.it)

Tax-payer code/VAT no. - IT01160480503

Declare that the machine:

Model - ***Elettropompa***

Type - ***EUR 3***


- complies with the requirements of Directive **2006/42/EC**, Annex **II**, section **A**, on the approximation of the laws of Member States relating to machinery;
- complies with essential requirements of the Directives:
  - **EMC 2004/108/EC** "Electromagnetic Compatibility", in application of Directive **95/54/EEC** "Measure Radiated Electromagnetic Emissions", and subsequent amendments;
  - **BT 2006/95/EC** "Low Voltage".

Also declares that:

- laboratory tests were carried out in accordance with the following standards:
  - CEI EN 61000-6-4 (2002/10), CEI EN 61000-6-2 (2000/02); CEI EN 61000-3-2 (2002/04); CEI EN 61000-3-3 (1997 / 12), CEI EN 60204-1 (1998/04), CEI EN 50178 (1999/03);

San Miniato Basso lì, July 2013

Il Legale Rappresentante  
Ciaponi Lido



It is useful to remember that the Declaration of Conformity is valid only if:

- The indications, safety warnings and instructions given in the operation and maintenance manual are observed.
- The system is used in accordance with the instructions provided by the manufacturer.
- Adjustment operations are carried out by authorized, trained and qualified personnel.
- Maintenance operations are carried out by qualified and authorized technicians.

Failure to comply with the requirements listed in the Certificate of Conformity shall automatically invalidate the warranty.

#### *1.1.0) RECOMMENDED USE*

Centralized lubrication systems are designed to automatically lubricate points subject to wear, after their identification.

Therefore, they must be used only for the lubrication of the points to which they are connected.

- Users are not allowed to apply unauthorized changes to an installed system. Modifications must be carried out or authorized by the manufacturer only.
- The system should always be used within the operating parameters specified in paragraph **1.4.0) TECHNICAL SPECIFICATIONS.**
- The system must be used only with the fluids listed in paragraph **2.3.1) LUBRICANTS.**
- The Technical Department of **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** can be contacted for further information or feasibility studies.

The manufacturer shall not be responsible for damages originating from an improper use or the unauthorized modification of the system or its components.

Furthermore, the manufacturer shall not be responsible for damages originating from the use of non original spare parts or parts not certified by the manufacturer, or for damages originating from the use of lubricants other than those listed.

### 1.2.0) SAFETY



- An improper use of the centralized lubrication system may cause damage due to an excessive or inadequate lubrication of the points to which it is connected.
- It is always necessary to comply with accident prevention and environmental regulations in force in the country where the centralized lubrication system is used.



### 1.3.0) DESCRIPTION OF THE SYSTEM

Figure 3 shows a schematic of the centralized lubrication system in its basic configuration.

The system comprises the following units:




Figure 3

**A – Electropump with tank**

**B – Main pipe**

**C – Multiple way dispenser**

**D – Secondary pipes**

Centralized lubrication systems significantly reduce the maintenance costs of the equipment on which they are installed, lowering downtime for maintenance operations and increasing the life of lubricated components.

These systems also enable to reach all the points that require lubrication, including those that are not accessible to operators.




Figure 4

If the pump is active, the pump conveys the lubricant into the main pipe of the pumping element, to supply the dispenser, which has to divide and dose the amount of lubricant among the points that have to be lubricated because subject to wear.

The secondary pipes distribute the lubricant to the fittings that replace the lubricators in the points subject to wear.

The diagram in Figure 4 shows the operating cycle of a centralized lubrication system.

The system can be operated both in manual or automatic mode, driven by the machine on which it is installed or by a control timer fitted inside the pump.

Each system is identified by means of a serial number stamped on the EC label, under serial number/year of manufacture.

- The serial number of the system must always be quoted when requesting technical information or ordering spare parts.

#### 1.4.0) TECHNICAL SPECIFICATIONS

The paragraphs that follow list the technical specifications of each component of the system.

##### 1.4.1) ELECTROPUMP




Figure 4

Electropump **EUR 3** is a piston pump driven by an eccentric cam, designed to operate with grease or oil, that can be used with a maximum of three pumping elements (Figure 5 ref. **A**, **B**, **C**) connected to the lubrication centralized.

The housing of the pump is a compact monobloc element in plastic, shaped in order to offer a full resistance to mechanical stresses.

The tank (figure 5 ref. **D**) is transparent polycarbonate molded for versions 2 liter and modular (figure 5 ref. **E**) for versions 4 and 8 liters.

The filling of the tank takes place by means of a special lubricator (figure 5 ref. **F**) situated in the front part of the pump body for versions grease and through a screw cap (figure 5 ref. **G**) on the top of the tank for oil versions.

Adhesive straps on the outside of the tank enable to easily identify the minimum and maximum levels.

The shaped roller system and windscreen wiper enable to eliminate air bubbles from the grease contained inside the tank, thus ensuring a trouble-free operation also at low temperatures.

The worm reduction gear with helical wheel and DC low voltage electric motor can be controlled directly or through the control timer (figure 5 ref. **H**).

The electric model **EUR 3** can be supplied in various versions characterized by the supply voltage (12 to 24 V DC; 110 ÷ 220 V AC), by the capacity of the tank (2 ÷ 4 ÷ 8 liters), by the control system with or without timer programming, by the presence or less of the sensor end of the cycle, by the presence or less of the warning of minimum level of grease in the tank.

Electrical connections are made through wired systems (Figure 5 ref. **I**).

**TABLE A** lists the codes of all the models of supply pumps.

*Table A*

Capability Voltage	Without Timer			Pause / Operating Timer			Pause / Sensor Timer		
	2 liters	4 liters	8 liters	2 liters	4 liters	8 liters	2 liters	4 liters	8 liters
12V	150102	150104	150108	150152	150154	150158	150202	150204	150208
24V	150252	150254	150258	150302	150304	150308	150352	150354	150358
110V	150402	150404	150408	150452	150454	150458	150502	150504	150508
220V	150552	150554	150558	150602	150604	150608	150652	150654	150658
12V	160102	160104	160108	160152	160154	160158	160202	160204	160208
24V	160252	160254	160258	160302	160304	160308	160352	160354	160358
110V	160402	160404	160408	160452	160454	160458	160502	160504	160508
220V	160552	160554	160558	160602	160604	160608	160652	160654	160658

For versions with optional device **MINIMUM LEVEL** code becomes:

- 1 5 1 ..... for all grease versions
- 1 6 1 ..... for all oil versions
- 1 7 1 ..... device press grease only grease version with tank 4 liters and supply voltage 24V



Grease

Oil

The technical specifications for electropump **EUR 3** are listed below:

- Operating temperature \_\_\_\_\_ From – 30°C to + 80°C
- Number of outlets \_\_\_\_\_ 1, 2 or 3
- Pumping system \_\_\_\_\_ Ø 6 mm piston, driven by eccentric cam
- Connection of main pipe \_\_\_\_\_ Quick fitting, for Ø 6 mm pipe
- Tank capacity \_\_\_\_\_ 2, 4, 8 liters with maximum and minimum level indicators
- Lubricant \_\_\_\_\_ Grease up to consistency grade **NLGI 2**  
Oil **50 – 1000 cST 40°C**
- Tank filling \_\_\_\_\_ With lubricator A M10x1 UNI 7663
- System for the removal of air bubbles \_\_\_\_\_ Rotating cylinder and windscreen wiper
- Capacity per outlet \_\_\_\_\_ See paragraph 1.4.2) *Pumping element*
- Reduction gear \_\_\_\_\_ Worm, with helical wheel and DC shielded electric motor
- Rated voltage \_\_\_\_\_ 24 V DC ; 12 V DC
- Rated absorption \_\_\_\_\_ 24 V DC – 0,5A ; 12 V DC – 1 A
- Max pickup absorption \_\_\_\_\_ 24 V DC – 3 A ; 12 V DC – 6,5 A
- Speed \_\_\_\_\_ 22 rpm
- Power supply \_\_\_\_\_ 12 V DC ; 24 V DC ; 110/220 V AC – 50 Hz
  - Rated absorption: 220V AC \_\_\_\_\_ 0,1 A
  - 110V AC \_\_\_\_\_ 0,2 A
- Protection class \_\_\_\_\_ IP65
- Control system \_\_\_\_\_ None, Timer or Timer and Sensor
- Device minimum level \_\_\_\_\_ Optional for all versions

**TABLE B** is shown for each model, the empty weight of the pump in standard configuration with a single pump installed:

**Table B**

Lubricant	GREASE	Tank capability	Weight
		2 liters	3,3 kg
OIL	OIL	4 liters	4,8 kg
		8 liters	5,5 kg
		2 liters	3,6 kg
		4 liters	5,1 kg
		8 liters	5,8 kg

The following diagram shows for each model the maximum dimensions of pump expressed in [mm]:




Figure 5

### 1.4.2) PUMPING ELEMENT

The pumping element is the working component of the pump. It is shrunk-fitted directly on the pump housing and driven by means of an eccentric cam. The suction system consists of a dual free channel, while the discharge has an adjustable delivery valve.




Figure 6

The piston contains a safety and discharge valve that immediately discharges the fluid inside the pumping element to avoid the building of excessive pressure that could potentially damage the system in the event of failure.

The components of the pumping element are in premium quality alloyed steel, treated to offer a high resistance to wear. A special superficial coating guarantee excellent resistance to corrosion, which is tested by means of salt spray tests. In the figure is shown the working scheme.




Figure 7

Completed the pumping phase of the delivery valve closes, facilitated by the spring. The return of the piston at BDC (bottom dead center) creates a vacuum inside the suction chamber cylinder, through which the lights **A** is filled with grease, Figure 8 left highlighted in light blue. The piston begins pumping phase, overcoming the backpressure created by the discharge valve and pumping the fat **B** in the plant.

The technical specifications of the pumping element are:

- Bore \_\_\_\_\_  $\varnothing = 6 \text{ mm}$
- Useful stroke \_\_\_\_\_ 6 mm
- Capacity \_\_\_\_\_  $0,17 \text{ cm}^3$
- Flow rate<sup>1</sup> \_\_\_\_\_  $\sim 2,8 \text{ cm}^3/\text{min}$
- Weight \_\_\_\_\_ 250 gr
- Safety valve \_\_\_\_\_  $P_{\max} = 250 \pm 50 \text{ bar}$
- Fitting \_\_\_\_\_ Standard with G1/4" threading

Figure 8 shows a pumping element with fitting for the connection of the main pipe, which is supplied as standard.




Figura 9

The main components are:

1. Pumping element
2. Washer
3. 90° fitting
4. Manual lubricator
5. Cap

It is therefore advisable to:




- Avoid changing the set points of the safety and delivery valve of the pumping element.
- **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** shall not be responsible for damages originating from the tampering with the safety valve.
- In the event of problems, immediately contact the **Customer Service**.

<sup>1</sup> Warning - the flow value mentioned relates to the following conditions: lubricating grease consistency class NGLI2 or oil 50-1000 cSt 40 °C, standard ambient conditions (T = 20 °C, p = 1atm), back pressure of 100 bar and motor from 20 rpm and rated voltage 12/24 V DC.

- **SIGNALING VALVE (with recirculation of grease)**

Figure 9 shows a version of the pumping element, which can be supplied as optional, with an external signaling system that controls the inlet instead of the safety valve with recirculation of grease.



The components shown are:

1. Pumping
2. Washer
3. 3 way shunt
4. Signaling valve
5. 90° fitting
6. Manual lubricator
7. Cap

Figura 10

In ordinary operating conditions, the external signaling valve is located in the inactive position (OFF – Spin down).

At the moment in which the pressure output from the pump reaches the value of 250 bar, the valve moves progressively in signaling position. (ON – Spin high).

After you restore the correct functioning of the system is necessary to verify that the indicator has returned to normal operating position.

In the event of overpressure circuit, the grease falls into the pump from the pumping itself.



- Do not modify or remove the safety valve outside.
- **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** disclaims any liability for damage caused by tampering with the safety valve outside.
- In case of malfunction of the safety valve outside immediately contact **Customer Service**.

- **SIGNALING VALVE (with ejection grease)**

Figure 11 shows a version of the pumping element, which can be supplied as optional, with an external signaling system that controls the inlet instead of the safety valve with ejection of grease.




Figura 11

The components shown are:

1. Pumping
2. Washer
3. 3 way shunt
4. Signaling valve
5. 90° fitting
6. Manual lubricator
7. Cap

At the moment in which the

pressure output from the pump reaches the value of 250 bar, the valve moves progressively in signaling position. (ON – Spin high). The centralized lubrication system is downloaded with grease leakage.

After you restore the correct functioning of the system is necessary to verify that the indicator has returned to normal operating position.

In the event of overpressure circuit, the grease falls into the pump from the pumping itself.



- Do not modify or remove the safety valve outside.
- **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** disclaims any liability for damage caused by tampering with the safety valve outside.
- In case of malfunction of the safety valve outside immediately contact **Customer Service**.

• **MANOMETER**

- Figure 12 shows the version of the pump, supplied as optional on request, with manometer for measuring the pressure delivered.




Figura 12

The components shown are:

1. Pumping
2. Washer
3. 3 way shunt
4. Manometer
5. 90° fitting
6. Manual lubricator
7. Cap

### 1.4.3) PIPES

The main pipe is supplied in meters with recyclable bushing that have to be assembled during the installation of the system or optionally with pressure bushings.

The operations required to assemble recyclable bushings are described in paragraph 1.4.5) FITTINGS.

Even secondary pipes are supplied by meters.

All pipes are supplied with lubricant in order to prevent the formation of air bubbles. The characteristics of the lubricant are specified in paragraph 2.3.1) LUBRICANTS.

The table that follows lists the codes for the main and secondary pipes used for the centralized lubrication system.

Code	Description	Length
00630	Main pipe R7 – 3/16	By meters
00760	Main pipe R7 – 1/8	By meters
097000	Secondary pipe ø6x1,5	By meters

**IMPORTANT:** To order a main pipe with pressure bushings, use the code **00630/00760** associated to the description **pressure bushings** and indicate a length in millimeters.

#### • MAIN PIPE




Figura 13

The main pipe is used to connect the pumping element to the progressive dispenser. This pipe consists in an hydraulic anti-abrasive pipe with very high chemical and physical characteristics, with a sub-layer in thermoplastic polyester, a reinforcement consisting in 2 polyester braids and in black polyurethane thermoplastic and pre-drilled coating. The polyurethane used for external coating offers a high resistance to abrasion and environmental agents (i.e. salt water, micro-bacteria, ozone, etc.). The technical specifications of the main pipe are:

- Compliant to standards	SAE J517, sez. SAE 100 R7 – EN855 – ISO3949
- Main pipe code	<b>00630</b>
- External diameter	3/16 inch / 9,6 mm
- Operating temperature	from - 40°C to + 93°C
- Minimum burst pressure at 20°C	~ 840 bar
- Minimum bending radius	25 mm
- Weight	60 gr/m
	<b>00760</b>
	1/8 inch / 8,2 mm
	from - 40°C to + 93°C
	~ 840 bar
	25 mm
	45 gr/m

- **SECONDARY PIPE**




Figura 14

The 6x1.5 secondary pipe is a type A, single layer pipe in Hytrel elastomeric polyester, compliant with the specifications listed in standards ISO, SAE, DIN, N.F. and UTAC.

The technical specifications for the secondary pipe are:

- Dimensions \_\_\_\_\_ Ø 6 mm x 1,5 mm
- Operating temperature \_\_\_\_\_ from - 40°C to + 80°C
- Minimum burst pressure at 20°C \_\_\_\_\_ ~ 150 bar
- Minimum bending radius \_\_\_\_\_ 20 mm

#### 1.4.4) DISPENSER




Figura 15

Modular distributors or volumetric dispensers used are progressive dispensers with check valve. They are made of a monobloc steel body containing small pistons in tempered steel, which divide the flow rate between the outlets.

Elements are sealed by means of high resistance O-Rings.

The progressive distributor can be supplied both assembled and disassembled.

The number of single dispensing elements which constitute a progressive distributor ranges from a minimum of 3 to a maximum of 10.

- SCREW TIE-RODS FOR DISPENSENSERS (screws UNI5931)

<b>TIE-RODS</b>	
<b>Code</b>	<b>Description</b>
00803	Tie-rods for 3 dispensing elements - M6x65
00804	Tie-rods for 4 dispensing elements - M6x80
00805	Tie-rods for 5 dispensing elements - M6x90
00806	Tie-rods for 6 dispensing elements - M6x110
00807	Tie-rods for 7 dispensing elements - M6x120
00808	Tie-rods for 8 dispensing elements - M6x140
00809	Tie-rods for 9 dispensing elements - M6x150
00810	Tie-rods for 10 dispensing elements - M6x170



The table that follows, which refers to figure 15, lists the codes for the necessary components of a progressive distributor.

Codes are also provided for the spare parts.

Pos	Code	Description
<b>A</b>	095500	Initial element
<b>B</b>	095502	Dispensing element 0,05 cm <sup>3</sup>
	095503	Dispensing element 0,10 cm <sup>3</sup>
	095504	Dispensing element 0,25 cm <sup>3</sup>
<b>C</b>	095505	End element
<b>D</b>	Da commercio	See the previous table
<b>A<sub>1</sub></b>	095020	Gasket set initial element
<b>B<sub>1</sub></b>	095019	Gasket set dispensing element
<b>C<sub>1</sub></b>	095527	Outlet cap
-----	095016	Sensor cap




Figura 1

Tab. C			
N	Dimensions (mm)		Weight (gr)
	A	B	
3	79,1	59,1	1230
4	93,8	73,8	1450
5	108,5	88,5	1670
6	123,2	103,2	1890
7	137,9	117,9	2110
8	152,6	132,6	2330
9	167,3	147,3	2550
10	182,0	162,0	2770





Figura 1


**TABLE E**, which refers to Figure 15, specifies the overall dimensions and the weight of the progressive dispenser without fittings, depending on the number "N" of dosing elements.

The technical specifications of the progressive dispenser are:

- Number of dispensers that can be assembled \_\_\_\_\_ from 3 to 10
- Operating temperature \_\_\_\_\_ from - 30°C to + 100°C
- Operating pressure: min \_\_\_\_\_ 10 bar
- max \_\_\_\_\_ 400 bar
- Max number of cycles per minute \_\_\_\_\_ 300
- Dispenser flow rate per cycle \_\_\_\_\_ 0,05 cm<sup>3</sup> ; 0,10 cm<sup>3</sup> ; 0,25 cm<sup>3</sup>
- Inlet fitting \_\_\_\_\_ M10x1 threading
- Outlet fitting \_\_\_\_\_ M10x1 threading
- Cycle electric control (optional) \_\_\_\_\_ By means of the sensor connected to the pause/operating



The following diagram describes the operation principle of taking as reference a distributor composed of 3 dispensers. The distribution and the flow rate to the various outputs is determined by the reciprocating movement of the pistons indicated with the letters "A", "B" and "C". With the stretch in black is identifies the flow of pressurized lubricant that determines the movement of the pistons.



The progressive distributor is powered by a pumping element of the pump EUR3, to which it is connected through the main pipe.

The dashed path identifies the flow of lubricant prepared for dispensing.

The course identifies the white pipes in which the lubricant is not under pressure.

The progressive numbering from 1 to 6 identifies the outputs of which are connected to the secondary pipes that carry the lubricant flow in the flow required to lubricate the various points bearing.

The stretch in white identifies the ducts in which the lubricant is not under pressure. The progressive numbering from **1** to **6** identifies the outputs of which are connected to the secondary pipes that carry the lubricant flow in the flow required to lubricate the various points bearing.

**STEP 1** - The flow of lubricant under pressure moves the piston "A" to the right enabling the delivery from the **1**.

This movement prepares the lubricant under pressure to the shift of the piston "B".

**STEP 2** - The resulting shift of the piston "B" to the right allows the delivery exit **4** and prepares the lubricant under pressure to the shift of the piston "C".


**STEP 3** - Moving to the right of the piston "C" allows allows the provision junction **6** and prepares the lubricant under pressure to the shift of the piston "A".

**STEP 4** - Moving to the left of the piston "A" allows the delivery from the **2** and prepares the lubricant under pressure to the displacement of the piston "B".

**STEP 5** - The shift of the piston "B" to the left allows the dispensing exit **3** and predisposes the lubricant under pressure to the shift of the piston "C".

**STEP 6** - The shift of the piston "C" to the left allows the delivery junction **5** and prepares the lubricant under pressure to the shift of the piston "A"

has been completed a lubrication cycle of the progressive distributor in question.



- ASSEMBLY

The dispenser must be assembled as shown in Figure 16. The initial element "A" dispenses "B" with the selected capacities, and the end element "C" must be paired correctly positioning the O-ring seal for each item.




Figura 16

In the table below we list the codes of the gaskets needed to assemble a progressive distributor:

Code	Pos	Description
095020	A <sub>1</sub>	Gasket set initial element
095019	B <sub>1</sub>	Gasket set dispensing element



It is useful to remember that the number of coupled dispensers can range between a minimum of 3 and a maximum of 10.

The tightening torque of the tie rods must be equivalent to 6 Nm (Newton per meter).

- **DOUBLING OF FLOW RATE**

The flow rate of each dispenser can be doubled by means of the internal connection of the two outputs. In this case it sees only one of the two outputs of the dispenser. For each lubrication cycle exit will be paid a nominal flow rate twice that shown on the dispenser. This operation, with reference to Figure 19, is performed by unscrewing the fitting from the side of the written "CX" from the doser to whom one wants to double the flow, phase "A", removing the threaded internal phase "B", and then screwing the plug M10x1, phase "C".





Figura 17



**IMPORTANT:** You cannot close both outputs on the same dispenser.

- **BRIDGE OUTPUT CONNECTION**




This connection system is used when we want to increase the flow of grease or oil, at a point of lubrication.

In carrying out this type of operation, you must always keep in mind the grain to the central liaison for doubling the flow rate, which in some combinations should be removed, while others must remain inside the dispenser.



In case of malfunctioning of the bridge link or problem about the installation, contact **Customer Service** immediately.

- **INDICATOR PULSE OF VISUAL INSPECTION**



The movement of the pin, actuated by the piston element on which is mounted the detector, as shown in the figure, allows visual control of the operation of the distributor and then the successful execution of the lubrication cycle.

The indicator is constructed in such a way that it can be installed on any

metering element of the distributor.

#### 1.4.5) FITTINGS


The fittings used for the centralized lubrication system includes both quick fittings and extensions, for secondary pipes with a diameter of Ø 6 mm, and recyclable fittings for the main pipe R7.

The paragraphs that follow describe the technical characteristics and dimensions expressed in millimeters for each type of fitting:


- **RECYCLABLE FITTING**

These fittings, which are made in steel or nickel-plated brass, are used to assemble the main pipe.


Code	Description	Ø	Ø1	CH	CH1	L
00591	Straight recyclable fitting Ø6 - 3/16" pipe	6	9,6	10	14	59



Code	Description	Ø	Ø1	CH	CH1	L1	L2
00592	90° recyclable fitting Ø6 - 3/16" pipe	6	9,6	12	14	36	57



Code	Description	Ø	Ø1	CH	CH1	L1
00750	Straight recyclable fitting Ø6 - 1/8" pipe	6	9,6	12	14	36



Code	Description	Ø	Ø1	CH	CH1	L1	L2
00751	90° recyclable fitting Ø6 - 1/8" pipe	6	9,6	10	12	36	51





Figura 19

Figure 18 show the operations that have to be performed to assemble the main pipe with recyclable fittings.


To facilitate and allow a correct assembly of the fitting, it is necessary to grease the internal and external surfaces of the area where the fitting is inserted.

- **QUICK FITTING**


Quick fittings are in nickel-plated brass.

The fitting, with conical metrical or gas threading, guarantees maximum sealing without the need of gaskets.


Code	Description	Ø	A	B	CH	L
096015	Straight fitting M6x1, conical	6	M6x1 con.	6	12	24,5
096016	Straight fitting M8x1, conical	6	M8x1 con.	6	12	23,5
096017	Straight fitting M10x1, conical	6	M10x1 con.	6	12	21
096022	Straight fitting G1/8"	6	G1/8"	7,5	12	21




Code	Description	Ø	CH	L
096021	Giunzione	6	12	33



Code	Description	Ø	A	B	CH	L1	L2
096018	90° fitting M6x1, conical	6	M6x1 con.	6	11	17	21
096019	90° fitting M8x1, conical	6	M8x1 con.	6	11	16,5	21
096020	90° fitting, M10x1 conical	6	M10x1 con.	6	11	16	21
096023	90° fitting G1/8"	6	G1/8"	7,5	11	17,5	21



Code	Description	Ø	A	B	CH	L1	L2
025030	90° fitting revolving M6X1	6	M6x1 con.	8	13	20,5	21,5
025031	90° fitting revolving M8X1	6	M8x1 con.	8	13	20,5	21,5
025032	90° fitting revolving M10X1	6	M10x1 con.	8	13	20,5	21,5
00426	90° fitting revolving G1/8	6	G1/8	7,5	12	21	22






Figura 20

The quick fitting accelerates the assembly and disassembly of the system pipes.


Figure 19 shows the operations that have to be performed to quickly assemble and disassemble the pipes.

Quick fitting pipes can be used both as recyclable fittings and as pressure bushings for the primary and secondary pipes.


### • EXTENSIONS

The tables that follow provide the codes of the straight and 90° extensions in brass, which can be installed on the secondary pipes of the centralized lubrication system.

Code	Description	A	A1	B	B1	CH	L
00460	Straight extension M6x1 con. - M10x1	M6x1 con.	M10x1	4.5	8	12	20
00499	Straight extension M8x1 con. - M10x1	M8x1 con.	M10x1	7	6	12	18
00448	Straight extension M10x1 con. - M10x1	M10x 1 con.	M10x1	7	6	12	18



Code	Description	A	A1	B	B1	CH	L1	L2
00380	90° extension M6x1 con. - M10x1	M6x1 con.	M10x1	7	4	12	20	12
00473	90° extension M8x1 con. - M10x1	M8x1 con.	M10x1	7	4	12	20	12
00430	90° extension M10x1 con. - M10x1	M10x1 con.	M10x1	7	4	12	20	12



The technical specifications of filling are:

- Operating temperature \_\_\_\_\_ From - 30°C to + 80°C
- Minimum pressure \_\_\_\_\_ -0,99 bar
- Maximum pressure \_\_\_\_\_ 150 bar
- Gas threads \_\_\_\_\_ Compliance with ISO7.1, BS 21, DIN 2999
- Metric/Conical threading \_\_\_\_\_ Compliance with UNI 7707

#### 1.4.6) TIMER

The timer is located inside the pump housing, in a waterproof area. Its function is to automatically control the centralized lubrication system.

Technical specifications for models with Pause/Operation timer, 24 V DC

- Operating voltage \_\_\_\_\_ 20 ÷ 30 V DC
- Maximum current load \_\_\_\_\_ 5 A
- Short-circuit limitation \_\_\_\_\_ 7 A
- Current absorbed in stand-by \_\_\_\_\_ 30 mA
- Current absorbed during the cycle \_\_\_\_\_ 50 mA (except current motor)
- Lamp power \_\_\_\_\_ 15 W (versions with remote control)
- Operating temperature \_\_\_\_\_ From - 25°C to + 70°C
- Storage temperature \_\_\_\_\_ From - 30°C to + 80°C
  - Overload limitation
  - Polarity inversion
  - Overheating
  - Overvoltage (max 45 V)
- Hardware protections \_\_\_\_\_
- Type of time memory \_\_\_\_\_ Digital type **EEPROM**
- Memory life \_\_\_\_\_ Unlimited
- Pause time setting \_\_\_\_\_ From 5 min to 12 hours through digital programming
- Working time setting \_\_\_\_\_ From 20 sec to 8 min through digital programming

#### WARNINGS:



- Power the timer by thoroughly following the instructions provided in 4.1.0) WIRING DIAGRAM.
- Do not power the timer with voltages above 35 V to prevent operating problems.



- **PAUSE/WORKING CYCLE**

The control of the working cycle is completely entrusted to the digital programming of the timer. After the pause time set, the system begins a cycle of length equal to the time of scheduled work.

The working time must be programmed in such a way that the duration of the lubrication cycle is sufficient to supply all the bearing points connected to it.

The time necessary for the completion of a lubrication cycle, can be determined by detaching the secondary pipe from any output of the progressive distributor and measuring the time elapsed between two successive deliveries.

 In case of difficulty in the determination of working time contact **Customer Service**.

- **PAUSE/SENSOR WORKING CYCLE**



The cycle control is assigned only to the Timer for programming the pause time. After the pause time set, the system begins the stage of lubrication. A proximity sensor or switch to induction, installed on the progressive distributor, reads the positions of the beginning and end of the cycle automatically stopping the operation of the pump.


In case of failure of plant operation, the Timer, after 10 minutes from the drive, it shall stop its operation.

A **control device remote** cod. **110001**, consisting of an illuminated push button installed on the control panel of the machine or vehicle, allowing the drive and verify the operation of the lubrication system.

 In case of difficulty in the determination of pause time contact **Customer Service**.

#### 1.4.7) SENSOR CONTROL WORKING DISTRIBUTORS

- **SENSOR CODE 095032 FOR AUTOMOTIVE APPLICATIONS**



*Figura 21*


The sensor code **095032**, normally used in the automotive sector, works as a button. Its output is an internal contact. It is used with the Sleep Timer – Sensor.

The cycle begins with the contact of the sensor locked: you spent the time programmed pause, the pump enters the stage of work (lubrication). The actuation of the dispenser installed on it opens the contact sensor that reads


the position of the beginning of lubrication cycle. The subsequent actuation of the dispenser will close the contact, and then the end of the work cycle, with a consequent stop of the pump.

The technical specifications of the standard sensor are:

- Degree of protection \_\_\_\_\_ IP68
- Contact \_\_\_\_\_ ON / OFF
- Operating temperature \_\_\_\_\_ From - 30°C to + 80°C



- **SENSOR CODE 095010 FOR INDUSTRY APPLICATIONS**



This sensor has been designed to control the correct functioning of progressive systems for the Industrial Sector.

The sensor checks the movement forward / return of the piston of the dispenser element.

During correct operation, with a regular supply by the distributor, the **LED** turns on and off alternately.

In case of malfunction, the sensor is blocked in a state where it is located (**LED** turned on or off according to the position).

The technical specifications of the standard sensor are:

- Degree of protection \_\_\_\_\_ IP67
- Operating temperature \_\_\_\_\_ From - 25°C to + 70°C
- Nominal distance of read \_\_\_\_\_ 5 mm
- Operating voltage \_\_\_\_\_ 10 ÷ 30 V DC
- Hysteresis \_\_\_\_\_ < 10% mm
- Max working frequency \_\_\_\_\_ 200 Hz
- Repeatability \_\_\_\_\_ < 0,01 mm
- Max output current into DC voltage \_\_\_\_\_ 100 mA
- Max load current \_\_\_\_\_ 200 mA
- Short circuit protection \_\_\_\_\_ Yes
- Led indicator \_\_\_\_\_ Yes
- Voltage drop \_\_\_\_\_ 1,8 V

- Loss of amperage \_\_\_\_\_ 1,8 mV
- Maximum pressure \_\_\_\_\_ 350 bar



- **N.B.: During maintenance or replacement of the sensor, it is recommended not to over-tighten the sensor itself, in fact, it should be positioned close to the mechanical but not forced.**

The electronic logic combined with sensor enables you to manage the alarm so visual, acoustic or cause, if necessary, to stop the system.

#### 1.4.8) MINIMUM LEVEL

The minimum level of grease in the tank is detected by a magnetic sensor **S** which detects the position taken during the work of the pump by a pivoting magnet **M**, as shown in the figure.

The principle of operation of the magnetic sensor is to on / off switch, normally open.

At the time of starting the pump, the system wiper rotates the magnet **M** pivoting.

The following two operating conditions may occur:

1. if the grease level in the tank is higher than the minimum level, the magnet pivoting **M**, due to the resistance offered by the grease to its progress, tends to tilt with respect to the vertical;
2. if the grease level in the tank is at the minimum level, the magnet pivoting **M** remains in a vertical position for effect of its own weight.




Figura 21

In the first case, the magnetic sensor **S** ignores the presence of the magnet **M** pivoting.

In the second case, the magnetic sensor **S** detects the presence of the magnet pivoting and **M** indicates the minimum level is reached in the tank of the grease.

In the pump without timer and with timer-pause, the signal detected by the system must be managed to control the machine on which you installed the centralized lubrication system (PLC).

In the pump with timer pause-sensor the signal detected is processed by the timer, which provides to instantly stop the centralized lubrication system, signaling the end of grease to an indicator light.

The detection of the position of the magnet **M** begins with a delay of approximately 20 sec. compared to the drive of the pump. The detection system the minimum level is provided by the manufacturer as an optional and does not provide for adjustment.

The detection of the position of the magnet **M** begins with a delay of approximately 20 sec. compared to the drive of the pump. The detection system of the minimum level is supplied as optional and are not provided for adjustment.

The electro-mechanical characteristics of the magnetic sensor **S** are:

- Mechanical life \_\_\_\_\_ 100 number of millions of cycles
- Switching frequency \_\_\_\_\_ 250 pulses/second
- Precision repeatability \_\_\_\_\_ 0,1 mm
- Operating temperature \_\_\_\_\_ From - 20°C to + 60°C
- Voltage \_\_\_\_\_ 100 V DC ÷ 150 V AC
- Max Power \_\_\_\_\_ 10 W
- Max current\* \_\_\_\_\_ 0,5 A

\*Do not use inductive loads greater than 0,1 A .

#### 1.5.0) STORAGE

The centralized lubrication system is usually supplied disassembled to customers.

Before forwarding the system, **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** adopts all the necessary measures to guarantee a correct packaging of all the components.

- ! • The user shall be responsible for storing all the components received by **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.**, indoors, in clean and dry rooms and at a safety distance from chemical and/or corrosive substances.
- ! • **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** shall not be responsible for damages originating from the incorrect storage of the components described.
- ! • It is useful to remember that the user is fully responsible for a safe loading, unloading and handling of the system.

#### 1.6.0) ASSEMBLY

The operating procedure that follows describes the operations that have to be carried out to assembly the centralized lubrication system.


For information on overall dimensions, weights and technical specifications of the single components, see Chapter 1.4.0) *TECHNICAL DATA* .


It is also useful to remember that:



- These operations must always be performed by trained and qualified technicians
- The protection and safety devices fitted on the vehicle or machine should not be modified or disabled. These devices may be removed during the installation of the system, but must be reinstalled after the installation has been completed.
- All centralized lubrication systems must be installed away from heat sources.
- Centralized lubrication systems should not be installed in particularly aggressive environments with chemicals that could potentially damage the components of the system.
- Welding and/or drilling operations required to install the centralized lubrication system must be performed in compliance with the technical specifications of the vehicle or machine manufacturer.
- Lubrication systems must be fitted only with the accessories supplied or certified by the Manufacturer.




#### 1.6.1) OPERATING PROCEDURE

F	Operation
0	Remove all the components of the system from the package.
1	Visually inspect all the components of the system in order to detect potential damages originating from transportation or from an improper storage.  All damages should be promptly reported to the <b>Customer Service</b> of <b>CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.</b>

F	Operation
<b>• ELECTROPUMP</b>	
2	<p>It is advisable to observe the following recommendations:</p> <div style="display: flex; align-items: center;"> <div style="flex: 1; margin-right: 20px;">  <p>ALTO</p> <p>112</p> <p>0°</p> <p>N°2 FORI Ø9</p> <p>FRONTALE</p> </div> <ul style="list-style-type: none"> <li>• Do not install the submerged pump in liquids or on supports with high vibrations.</li> <li>• Do not install the pump next heat sources or close to the electric equipment that could affect the correct operation of the control timer.</li> <li>• Do not install the pump in areas with explosive or inflammable mixtures.</li> <li>• Place electropump EUR 3 in the position shown in the figure.</li> <li>• Leave at least 100 mm from other equipment or obstacles that prevent access to the pump.</li> <li>• Install the pump making sure that the lubricator for the tank filling and the control timer are easily accessible.</li> <li>• Fix the pump to its support using the Ø 9 mm holes and the 2 M8 UNI5931 – 8.8 screws.</li> </ul> </div> <p>Note: it is also possible to use the <b>STANDARD ROD</b> (Code <b>00610</b>) available as optional on request.</p>


F	Operation
<b>• PUMPING ELEMENT</b>	
3	<p>The system is usually supplied with a single pumping element installed on outlet no. 2.</p> <p>The figure shows the sequence of operations that need to be performed to install the pumping element on outlet 1 and/or 3.</p> <p>• Loosen and remove the cap with gasket "A" from the outlet where the pumping unit has to be installed.</p> <p>• Insert and tighten the pumping element in the selected configuration "B".</p> <p>• Tighten the pumping element with a torque of 20 Nm.</p> 
<p><b>WARNING:</b> the position of the driving cam may hinder the tightening of the pumping element. In this case, it is necessary to install the pumping unit on one of the other outlets or introduce the pumping unit, making sure that the threads are correctly arranged.</p>	
<b>• FITTINGS</b>	
4	<p>Remove the lubricators from the bearing points of the automatic system that require lubrication.</p>
5	<p>Tighten the fittings of the bearing points.</p> <p><b>NB:</b> use extensions for the fittings if difficulties arise due to the lack of space or the incorrect positioning of fittings on the bearing points.</p>
6	<p>Tighten the fittings of the dispenser that has to be used.</p> <p><b>NB:</b> the dispenser is generally supplied without the outlet caps required for the dispensers. Otherwise, remove the screw caps.</p>
7	<p>Tighten the inlet fitting of the dispenser where the main pipe has to be connected.</p>

F	Operation
<b>• DISPENSER</b>	
8	 <p>Install the dispenser leaving a distance of at least 50 mm from equipment and obstacles that could prevent the access to the fitting of pipes.</p> <p>For models with sensor, place the dispenser in a position that allows the cables to be easily connected to the electropump.</p> <p>Fix the dispenser to the frame or crossbeams so that it is possible to reach the lubricating points of the bearing.</p> <p>To progressively fix the dispenser to its support, use holes "A" and "B", located on the initial and final sections of the assembled dispenser, and 3 M6 screws.</p>
<b>• SENSOR</b>	
9	 <p>Only for the version with Pause control timer/Sensor</p> <p><b>Sensor</b>, code <b>095032</b>, must be installed only on <math>0.25 \text{ cm}^3</math> dispensers.</p> <ul style="list-style-type: none"> <li>• Remove the screw cap with metal gasket "A".</li> <li>• Press the small piston until it reaches the limit switch; use a plug with a diameter of Ø6mm.</li> <li>• Tighten the sensor as shown in the figure.</li> </ul>
<b>• MAIN AND SECONDARY PIPES</b>	
10	<ul style="list-style-type: none"> <li>• Cut the pipes to measure at a straight angle using a cutter or a shearing unit.</li> <li>• Tagliare le tubazioni a misura con taglio ad angolo retto: utilizzare un taglierino con sistema di taglio a cesoia</li> </ul> <p><b>NB:</b> the pipe length should be calculated taking into account the minimum bending radius and the additional length required for the pipes fixed to mobile parts.</p>
11	<p>Fix the main and secondary pipes using common clips or straps.</p> <p><b>WARNING:</b> do not fix or thread the pipes on vehicle or machine components that could overheat (i.e. exhaust pipes, motor, etc.).</p>
12	Connect the pipes to the fittings.


F	Operation
13	<p><b>NB:</b> the main pipe is used to connect the pump to the dispenser; the secondary one is instead used to connect the dispensers to the bearing points that require lubrications.</p> <ul style="list-style-type: none"> <li>• <i>ELECTRICAL CONNECTION 12/24 V DC</i></li> <li>• <i>VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK</i></li> </ul> <p>The only connection this is the power supply.</p>  <p>The figure shows the <b>WIRING 2P power/sensor</b> code <b>150050</b> used for the connection. It is derived from the body of the pump marked <b>A</b>.</p> <ul style="list-style-type: none"> <li>• <i>VERSION WITH TIMER PAUSE/SENSOR</i></li> </ul>
14	  <p>The <b>CABLE 2P power/sensor</b> code <b>150050</b>, derived from the <b>S</b> of the pump body, must be connected to the connector <b>B</b> of the sensor. While derived from the connector to the pump housing must be connected to the electrical supply system and with the light button of the <b>remote control device</b> code <b>110001</b>.</p>

- VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK AND MINIMUM LEVEL


15



Connettore A




Connettore S




The **CABLE 2P power/sensor** code **150050** used for the connection is derived from the exit of the pump body marked with **A**. From the position **S** is instead derived **CABLE 2P minimum level** cod. **150051**.

- VERSION WITH TIMER PAUSE/SENSOR AND MINIMUM LEVEL


16



Connettore A



Connettore S



The **CABLE 2P power/sensor** code **150050**, derived from the **S** of the pump body, must be connected to the connector **B** of the sensor. While the connector (code **150053**) derived from the **A** of the pump casing must be connected to the electrical supply system and with the light button of the **remote control device** code **110001**. The minimum level signal is controlled by the electronic.

• *ELECTRICAL CONNECTION 110/220 V AC*

17

**WARNING:** for the powered versions 220/110V AC - 50Hz




- All electrical components of the system shall be grounded. This applies both to the electrical parts that for the control devices. To do this, make sure that the ground wire is properly connected. For safety reasons in case of accidental disconnection of wiring the ground wire should be the last to be removed: therefore, the ground wire should be about 100mm longer than the phase conductors.
- Connection to the mains supply must be carried out between the electrical wiring of the lubrication system and the power supply a suitably selective differential magneto dimensionat.

In the following procedures, always refer to paragraph 1.6.2) *WIRING DIAGRAM*

 • *VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK*

18




1) GIALLO/VERDE - Terra
2) BLU - Neutro
3) MARRONE - Fase




In the figure on the right is a diagram of a wiring connection is (code 150052). The cabling is derived from the **A** of the pump casing and comes with about 600 mm of the sheath.

## • VERSION WITH TIMER PAUSE/SENSOR


19



Connettore A



Connettore S




The cable (code **150056**) derived from the **A** of the pump body must be connected to the electrical supply system and with the light button of the **remote control device** code **110001**.


The harness comes with about 600 mm of the sheath. The **CABLE 2P power/sensor** code **150050**, derived from the **S** of the pump body, must be connected to the **B** sensor as for version **12/24 V DC**.

 • VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK AND  
MINIMUM LEVEL

20




Connettore S




The **CABLE 2P power/sensor** code **150050**, derived from the **S** of the pump body, is what sends the signal to the minimum level.

• VERSION WITH TIMER PAUSE/SENSOR AND MINIMUM LEVEL


21



Connettore A



Connettore S




The cable, derived from the **A** to the body pump, it must be connected to the electrical supply system and with the light button of the **remote control device** code. **110001**. The harness comes with about 600 mm of the sheath.

The **Cable 2P power/sensor** code. **150050**, derived from the **S** of the pump body, must be connected to the **B** sensor as for version **12/24 V DC**. The minimum level signal is controlled by the electronic control.

• REMOTE CONTROL DEVICE

22 For versions with **control timer pause/sensor**, install the luminous indicator of the **Remote control device** (Cod. **110001**) on the control board of the machine or vehicle



It is possible to use both the 12/24 V dc and 110/220 V ac remote control device.

The figure shows the wiring diagram for the luminous indicator.

For information on how to

connect the harness to the electropump, see the diagram referred to the selected version and the one below.


**NB:** a lamp with a voltage above 24 V should be used for 110/220 V AC versions.




23 Connect the electropump to the electric system of the vehicle or of the machine on which the lubrication system is installed.


## 1.6.2) WIRING DIAGRAM VERSION 12/24 V DC

## ▪ VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK




## ▪ VERSION WITH TIMER PAUSE/SENSOR



**1.6.3) WIRING DIAGRAM VERSION 110/-220 V DC**
**■ VERSION WITHOUT TIMER OR WITH TIMER PAUSE/WORK**


### *VERSION WITH TIMER PAUSE/SENSOR*




## PART 2 – OPERATING MANUAL

### 2.1.0) COMANDS

The table that follows describes the command and control devices of centralized lubrication systems with Pause/Operation timer and Pause/Sensor timer.

The figure shows the

devices installed on the Timer.



The pump of versions without timer are electrically powered by the system that drives them. In this case, start and control instructions are described along with the management and control instructions of the machine where the system is installed.

Pos.	Type	Description
1	Display	<ul style="list-style-type: none"> <li>It displays the parameters that have been set during the time setting procedure.</li> <li>The display LEDs turn on in sequence during ordinary operation.</li> </ul>
2	Led display	This LED turns on when the lubrication system is electrically powered.
3	Button TEST	<p>To access the timer, it is sufficient to slightly press it next to "Push". If it is pressed during ordinary operation, it starts the set working cycle after performing a self-diagnostic check. At the end of the working cycle, the timer returns to the Automatic mode.</p> <p>If it is pressed during the timer programming, it enables to scroll the options.</p>
4	Button ENTER	<ul style="list-style-type: none"> <li>If it is pressed for 3 seconds, it starts the digital programming procedure.</li> <li>If it is pressed briefly during the programming mode, it enables to change the P (pause) and L (working) values.</li> </ul>

Pos.	Type	Description
A remote control system is available as optional for systems with Pause - Sensor timer. This must be installed next to the control panel of the vehicle or the machine where the system is installed.		
-----	Luminous indicator, remote control device	<ul style="list-style-type: none"> <li>This indicator turns on when the centralized lubrication system is powered. It remains on for a few seconds until the timer has completed the initial check and then turns off.</li> <li>It blinks when the pump is running.</li> <li>It turns on when there is no grease in the tank or if a problem occurs on the system.</li> <li>If pressed during ordinary operation it starts a work cycle, after performing a self diagnostic test. Upon completion of the cycle, the timer returns to the Automatic mode.</li> </ul>

### 2.2.0) TIMER PROGRAMMING

The sections that follow summarize the operations that need to be performed to digitally program the control timer.

It is useful to remember that if a power outage occurs, the timer saves the internal data in a digital memory that has no expiry. As soon as power is restored, the timer reloads the saved data and starts counting the time from the point and status in which it had interrupted its operation.




Figura 23

Nº	Activity	Consequence
01	Loosen fixing screws "A" and remove the cover "B" to access the timer	This operation gives access to the timer for digital programming.
02	Press <b>ENTER</b> for 3 seconds	The display turns on and shows letter <b>P</b> (Pause).
03	Briefly press <b>ENTER</b>	The display shows the value set for parameter <b>P</b> .
04	Press <b>TEST</b> to change the value of parameter <b>P</b>	Every time the button is pressed, the displays shows in sequence the digits and letters of the pause time settings shown in the table.
05	Briefly press <b>ENTER</b> to confirm the setting	The displayed value is stored as current value for parameter <b>P</b> and the display shows once more letter <b>P</b> .
 • <b>NB.</b> For versions with Pause-Sensor control timer, skip directly to operation 10, because the only parameter that can be set is the pause time P.		
06	Press <b>TEST</b> to alternate the display of parameters <b>P</b> and <b>L</b>	<p>The display shows letter <b>L</b> (working time).</p> <ul style="list-style-type: none"> <li>• <b>NB:</b> it is useful to remember that <b>TEST</b> enables to alternate the display of letters <b>P</b> or <b>L</b>.</li> </ul>
07	Briefly press <b>ENTER</b>	The display shows the value set for parameter <b>L</b> .
08	Press <b>TEST</b> to change parameter <b>L</b>	Every time the button is pressed, the displays shows in sequence the digits and letters of the working time settings shown in the table.
09	Briefly press <b>ENTER</b> to confirm the selected setting	The displayed value is stored as current value for parameter <b>L</b> and the display shown once more letter <b>L</b> .
10	Press <b>ENTER</b> for 3 seconds	The display turns off and is ready to run with the new set parameters.
11	Remove cover "B" to access the timer and retighten screws "A"	The pump is ready to work.



**WARNING** - Electropumps with control timers have the following default settings:


- Pause **P = 8**
- Working time **L = 2**

Table with time settings

• PAUSE settings for pause P	
Display	Tempo
0	5 min
1	10 min
2	15 min
3	30 min
4	1 h
5	2 h
6	3 h
7	4 h
8	5 h
9	6 h
A	7 h
B	8 h
C	9 h
D	10 h
E	11 h
F	12 h

• WORK: settings for working times L	
Display	Tempo
0	20 sec
1	40 sec
2	1 min
3	1,5 min
4	2 min
5	2,5 min
6	3 min
7	3,5 min
8	4 min
9	4,5 min
A	5 min
B	5,5 min
C	6 min
D	6,5 min
E	7 min
F	8 min

### 2.3.0) TANK FILLING



*Figura 24*

The pump tank is filled by means of lubricator "A".

Remove the cap from the lubricator and fill the tank up to the maximum level (**MAX**), marked with an adhesive label on the tank.

For information on the characteristics of lubricants, see the following paragraph.

During the filling of the tank, verify that the air in it is discharged by means of the vent. Make sure that the vent, located on the rear of the tank, is not obstructed



### 2.3.1) LUBRIFICANTS

- It is useful to remember that systems manufactured by **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** are designed to be used with lubrications with a maximum grade of **NLGI 2**.
- Use only compatible lubricants with **NBR** gaskets.
- CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** supplies the system components that are already lubricated with **NLGI 2** lubricant.

Family description	NLGI grade	ASTM penetration at 25°C in 1/10 of mm
Fluid greases	000	445 – 475
Semi-fluid greases	00	400 – 430
Semi-fluid greases	0	355 – 385
Mild greases	1	310 – 340
Medium greases	2	265 – 295

The table provides comparative data between NLGI (National Lubricating Grease Institute) and ASTM (American Society for Testing and Materials) data only of the ranges used by the systems manufactured by **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.**. For further information on technical data and safety measures, see the **Product Safety Sheet** (Directive 93/112/EEC) related to the type of lubricant selected or supplied by the manufacturer

## 2.4.0) START-UP

The operating procedure described below briefly describes the operations that have to be performed to start the system.



**NB:** The following procedure should always be performed when:

- During the initial start-up following installation
- After every maintenance operation
- If the system has not been in operation for a considerable amount of time

## 2.4.1) OPERATING PROCEDURE

Nº	Activity	Consequence
Make sure that:		
0	Disconnect one or more secondary pipes from the bearing lubrication points	Verify that the lubricant reaches the bearing.
1	Press the manual Start button (TEST)	The pump performs one cycle.
2	Repeat the operation described above until the lubricant reaches all the lubrication points of the bearings from which the pipes have been disconnected	The lubricant dispensing system is running correctly.
3	Reconnect the pipes to the bearing lubrication points	The system is set in Automatic mode.
<b>• WARNING:</b> if the system is not operating correctly, see Chapter 3.3.0) ANOMALIES		



## PART 3 – MAINTENANCE INSTRUCTION

### 3.1.0) MAINTENANCE INSTRUCTION

This paragraph provides essential information to allow maintenance technicians to perform ordinary maintenance operation in full safety

Before performing any maintenance operation, operators should remember to:

• Verify	That the system is not running
• Check	That the electropump has been disconnected from the power supply
• Check	That the disconnection switch upstream from the electric cubicle has been disconnected
• Adopt	All the measures referred to in current accident prevention laws and specifically those necessary to signal that servicing operations are in progress.


### 3.2.0) SCHEDULED MAINTENANCE

Due to simplicity of design, robustness and reliability of the components used, **CIAPONI LUBRIFICAZIONE CENTRALIZZATA s.r.l.** recommends only a limited number of inspections and scheduled maintenance operations.

The table that follows lists the checks that have to be performed periodically, along with the frequency and type of operation that the technician must perform to guarantee the efficiency of the system in time.

CHECK	FREQUENCY	OPERATION
Tightening of components	After the first 500 hours	Check that all components have been correctly tightened.
Pipe fixing	After the first 500 hours Every 1500 hours	Check that the fittings have been installed Check that machine parts have been correctly installed
Operation of the electropump	Every 6 months	Check the operation of the electropump with button Test
Tank level	As required	Refill the lubricant in the tank
Filling filter	Every 2 fills	Check and replace (see following paragraph)

### 3.2.1) FILTER REPLACEMENT ONLY GREASE VERSION



*Figura 25*

To service the filling filter of the tank, it is necessary to remove cap "A", the lubricator "B" and filter "C".  
 Inspect the filter and clean it with compressed air, if necessary.  
 If the filter is still dirty after being cleaned, replace it.  
 Reassemble filter "C", lubricator "B" and cap "A".  
 Tighten the lubricator "B" with a maximum torque of 6 Nm.

### 3.3.0) ANOMALIES

This chapter provides information on:

- **Possible problems that may occur during the operation of the system**
- **The cause that may prevent the system from starting and stopping**
- **Corrective actions**



**NB:** the lubrication system with Pause/Sensor control timer has a luminous indicator that can be managed remotely. If the indicator stays on permanently at the end of an operating cycle:

- The grease in the tank may have fallen to the minimum level
- An anomaly has occurred within the system

In both cases, the Timer stops the system even after 10 minutes.

N	Problem	Code	Cause	Corrective action
01	The pump motor doesn't work	01.01	No current	Check the power supply and the status of the fuse.
		01.02	The electronic card is not working	Replace the electronic card.
		01.03	The reduction gear doesn't work	Replace the reduction gear.
02	The pump doesn't delivery lubricant	02.01	The tank is empty	Fill the tank with clean lubricant.
		02.02	Air bubbles in lubricant	Disconnect the primary tube of the fitting of the pumping element. Start the pump manually until the lubricant expelled from the fitting is not perfectly cleaned.

N	Problem	Code	Cause	Corrective action
		02.03	Unsuitable lubricant	Replace the lubricant with a suitable one
		02.04	Pumping unit element blocked	Disassemble the pumping element and clean the suction ducts
		02.05	Worn pumping element piston	Replace the pumping unit
		02.06	The delivery valve of the pumping unit is blocked	Replace the pumping unit
03	The pump runs, but no lubricant reaches the bearing lubrication points	03.01	Disconnect pipes	Check the status of the pipes and the connections to fittings. Replace worn pipes.
		03.02	The progressive dispenser is blocked	Replace the dispenser or clean it.
04	The lubricant is distributed to the bearing lubrication points irregularly	04.01	The dispenser is not correctly connected to the bearing lubrication points	Check that the dispensed amounts are compliant with those indicated in the system diagram.
		04.02	The pause is not correctly set	
05	The display LED is on	05.01	The supply voltage is not correct	Verify that the supply voltage ranges between 20V DC and 30V DC, otherwise adjust the supply system.
06	The motor doesn't start when TEST is pressed	06.01	The motor is not correctly connected to the timer	Check the cables that connect the electric motor to the timer and restore connections.
		06.02	The motor is not working correctly	Check that the motor is not short-circuited and that it does not absorb a current above 7A. Replace the reduction gear.
07	The display LEDs alternate but the motor doesn't run	07.01	Faulty motor	Contact the Customer Service.
08	The pump starts the greasing phase but doesn't complete it immediately	08.01	Faulty motor or high output absorption	Allow the pump to cool down for a few minutes and retry. If the problem reoccurs, contact the Customer Service.


## PART 4 – SPARE PARTS

The diagram below shows the key to reading the tables of identification of spare parts.

- WARNING:** to require the provision of spare parts necessary to specify, in addition to the code of the particular request, the serial number of the system used and the version number, obtainable from the nameplate for CE marking, as shown in the figure.



Figura 22






Table 00

Table 01




Table	00	Parts list for all version supplied to 12/24V DC	Version	150102	150104	150108	150152	150154	150158	150202	150204	150208	150252	150254	150258	150302	150304	150308	150352	150354	150358
Group	0		Q	"Blue" = present; White" = missing																	
Pos	Code	Description	Q																		
00.01	150000	Body pump <sup>2</sup> <i>Corpo pompa</i>	1																		
00.02	093001	Oil seal 22x10x7 <i>Paraolio 22x10x7</i>	1																		
00.03	150001	Washer <i>Rosetta</i>	3																		
00.04	105020	Gearmotor 12V DC <i>Motoriduttore 12V DC</i>	1																		
	105021	Gearmotor 24V DC <i>Motoriduttore 24V DC</i>	1																		
00.05	150011	Screw M6x25 <i>Vite M6x25</i>	3																		
00.06	093011	Washer 10x30x2,5 DIN9021 <i>Rosetta 10x30x2,5 DIN9021</i>	1																		
00.07	093007	Feather key 3x5 UNI6606 <i>Chiavetta 3x5 UNI6606</i>	1																		
00.08	092299	Assembly cam <i>Assieme camma</i>	1																		
00.09	093012	Assembly holed disc <i>Assieme disco forato</i>	1																		

<sup>2</sup> Warning: for version with minimum level the code is: .....

Table	00	Parts list for all version supplied to 12/24V DC	Version	150102	150104	150108	150152	150154	150158	150202	150204	150208	150252	150254	150258	150302	150304	150308	150352	150354	150358
Group	0		Q	"Blue" = present; "White" = missing																	
Pos	Code	Description	Q																		
00.10	093013	Bearing 6000 <i>Cuscinetto 6000</i>	1																		
00.11	093043	Holed disc <i>Disco forato</i>	1																		
00.12	150003	Screw M6x20 DIN7991 <i>Vite M6x20 DIN7991</i>	2																		
00.13	150004	Assembly brush windscreen <sup>3</sup> <sup>4</sup> <i>Assieme paletta tergi vetro</i>	1																		
00.14	093045	Cap outlet pumping <i>Tappo uscita pompante</i>	2																		
00.15	093027	O-Ring 4081 <i>O-Ring 4081</i>	2																		
00.16	093028	Pumping cap M22x1,5 <i>Tappo M22x1,5</i>	2																		
00.17	093031	Filter 300 µm <i>Filtro 300µm</i>	1																		
00.18	093032	Lubricator A M10x1 UNI7663 <i>Ingrassatore A M10X1 UNI7663</i>	1																		
00.19	150010	Lubricator cap <i>Tappo ingassatore</i>	1																		
00.20	150006	Cover full timer <i>Coperchio Timer completo</i>	1																		
00.21	150025	Seal cover Timer <i>Guarnizione coperchio Timer</i>	1																		
00.22	150024	Cover Timer <i>Coperchio Timer</i>	1																		
00.23	150007	Screw 2.9x9.5 DIN7981 – Stainless steel <i>Vite 2.9x9.5 DIN7981 – Inox</i>	4																		
00.24	150008	Carter gearmotor complete <i>Carter motoriduttore completo</i>	1																		
00.25	100027	Seal <i>Guarnizione</i>	1																		
00.26	100028	Carter gearmotor <i>Carter motoriduttore</i>	1																		
00.27	150009	Screw 6x20 ISO7380-10.9 DAC500 <i>Vite 6x20 ISO7380-10.9 DAC500</i>	7																		
00.28	093022	O-Ring 4550 <i>O-Ring 4550</i>	1																		

Table	01	Parts list cable and timer for all version supplied to 12/24V DC	Version	150102	150104	150108	150152	150154	150158	150202	150204	150208	150252	150254	150258	150302	150304	150308	150352	150354	150358
Group	0		Q	"Green" = present ; "White" = missing																	
Pos	Code	Description	Q																		
01.01	150070	Timer P/L 12V/24V DC <i>Timer P/L 12V/24V DC</i>	1																		
	150072	Timer P/S 12V/24V DC <i>Timer P/S 12V/24V DC</i>																			

<sup>3</sup> **WARNING:** for version with minimum level the code is: .....

<sup>4</sup> **WARNING:** for version with increased tank see Table 03

Table	01	Parts list cable and timer for all version supplied to 12/24V DC	Version	150102	150104	150108	150152	150154	150158	150202	150204	150208	150252	150254	150258	150302	150304	150308	150352	150354	150358
Pos	Code	Description	Q	"Green" = present ; "White" = missing																	
01.02	150050	Supply/sensor cable 2P <i>Cablaggio 2P alimentazione/sensore</i>	1																		
01.03	150057	Supply cable 4P <i>Cablaggio 4P alimentazione</i>	1																		

Table	01	Parts list cable and timer for version supplied to 12/24V DC with minimum level	Version	151102	151104	151108	151152	151154	151158	151202	151204	151208	151252	151254	151258	151302	151304	151308	151352	151354	151358
Pos	Code	Description	Q	"Green" = present; "White" = missing																	
01.01	150070	Timer P/L 12V/24V DC <i>Timer P/L 12V/24V DC</i>	1																		
	150072	Timer P/S 12V/24V DC <i>Timer P/S 12V/24V DC</i>																			
01.02	150050	Supply/sensor cable 2P <i>Cablaggio 2P alimentazione/sensore</i>	1																		
01.03	150057	Supply cable 4P <i>Cablaggio 4P alimentazione</i>	1																		
01.04	150051	Minimum level cable 2P <i>Cablaggio 2P minimo livello</i>	1																		




Table A0




Table A1

Table	AO	Parts list for all version supplied to 220/110V AC	Version	150402	150404	150408	150452	150454	150458	150502	150504	150508	150552	150554	150558	150602	150604	150608	150652	150654	150658
Group	O		Q	"Blue" = present; "White" = missing																	
Pos	Code	Description	Q																		
A0.01	150000	Body pump <sup>5</sup> <i>Corpo pompa</i>	1																		
A0.02	093001	Oil seal 22x10x7 <i>Paraolio 22x10x7</i>	1																		

<sup>5</sup> **Warning:** for version with minimum level the code is: .....

Table	AO	Parts list for all version supplied to 220/110V AC	Version	150402	150404	150408	150452	150454	150458	150502	150504	150508	150552	150554	150558	150602	150604	150608	150652	150654	150658	
Group	O		Q	"Blue" = present; "White" = missing																		
Pos	Code	Description	Q																			
A0.03	150001	Washer <i>Rosetta</i>	3																			
A0.04	105020	Gearmotor 12V DC <i>Motoriduttore 12V DC</i>	1																			
	105021	Gearmotor 24V DC <i>Motoriduttore 24V DC</i>																				
A0.05	150011	Screw M6x25 <i>Vite M6x25</i>	3																			
A0.06	093011	Washer 10x30x2,5 DIN9021 <i>Rosetta 10x30x2,5 DIN9021</i>	1																			
A0.07	093007	Feather key 3x5 UNI6606 <i>Chiavetta 3x5 UNI6606</i>	1																			
A0.08	092299	Assembly cam <i>Assieme camma</i>	1																			
A0.09	093012	Assembly holed disc <i>Assieme disco forato</i>	1																			
A0.10	093013	Bearing 6000 <i>Cuscinetto 6000</i>	1																			
A0.11	093043	Holed disc <i>Disco forato</i>	1																			
A0.12	150003	Screw M6x20 DIN7991 <i>Vite M6x20 DIN7991</i>	2																			
A0.13	150004	Assembly brush windscreen <sup>6</sup> <sup>7</sup> <i>Assieme paletta tergi vetro</i>	1																			
A0.14	093045	Cap outlet pumping <i>Tappo uscita pompanente</i>	2																			
A0.15	093027	O-Ring 4081 <i>O-Ring 4081</i>	2																			
A0.16	093028	Pumping cap M22x1,5 <i>Tappo M22x1,5</i>	2																			
A0.17	150055	Raddrizzatore	1																			
A0.18	150053	Trasformatore 110V AC/ 24V DC	1																			
	150054	Trasformatore 220V AC/ 24 V DC																				
A0.19	093031	Filter 300 µm <i>Filtro 300µm</i>	1																			
A0.20	093032	Lubricator A M10x1 UNI7663 <i>Ingrassatore A M10X1 UNI7663</i>	1																			
A0.21	150010	Lubricator cap <i>Tappo ingassatore</i>	1																			
A0.22	150006	Cover full timer <i>Coperchio Timer completo</i>	1																			
A0.23	150024	Seal cover Timer <i>Guarnizione coperchio Timer</i>	1																			
A0.24	150025	Cover Timer <i>Coperchio Timer</i>	1																			
A0.25	150007	Screw 2.9x9.5 DIN7981 – Stainless steel <i>Vite 2.9x9.5 DIN7981 – Inox</i>	4																			
A0.26	100028	Carter gearmotor complete <i>Carter motoriduttore completo</i>	1																			
A0.27	100027	Seal <i>Guarnizione</i>	1																			

<sup>6</sup> **WARNING:** for version with minimum level the code is: .....


<sup>7</sup> **WARNING:** for version with increased tank see Table 03

Table	AO	Parts list for all version supplied to 220/110V AC	Version	150402	150404	150408	150452	150454	150458	150502	150504	150508	150552	150554	150558	150602	150604	150608	150652	150654	150658
Group	O		Q	"Blue" = present; "White" = missing																	
Pos	Code	Description	Q																		
A0.28	150008	Carter gearmotor <i>Carter motoriduttore</i>	1																		
A0.29	150009	Screw 6x20 ISO7380-10.9 DAC500 <i>Vite 6x20 ISO7380-10.9 DAC500</i>	7																		
A0.30	093022	O-Ring 4550 <i>O-Ring 4550</i>	1																		

Table	A1	Parts list cable and timer for all version supplied to 220/110V AC	Version	150402	150404	150408	150452	150454	150458	150502	150504	150508	150552	150554	150558	150602	150604	150608	150652	150654	150658
Group	O		Q	"Green" = present ; "White" = missing																	
Pos	Code	Description	Q																		
A1.01	150070	Timer P/L 12V/24V DC <i>Timer P/L 12V/24V DC</i>	1																		
	150072	Timer P/S 12V/24V DC <i>Timer P/S 12V/24V DC</i>																			
A1.02	150052	Cable 3P <i>Cablaggio 3P</i>	1																		
A1.03	150056	Supply cable 4P+3P <i>Cablaggio 4P+3P alimentazione</i>	1																		
A1.04	150050	Supply/sensor cable 2P <i>Cablaggio 2P alimentazione/sensore</i>	1																		

Table	A1	Parts list cable and timer for version supplied to 220/110V AC with minimum level	Version	151402	151404	151408	151452	151454	151458	151502	151504	151508	151552	151554	151558	151602	151604	151608	151652	151654	151658
Group	1		Q	"Green" = present; "White" = missing																	
Pos	Code	Description	Q																		
A1.01	150070D	Timer P/L 12V/24V DC <i>Timer P/L 12V/24V DC</i>	1																		
	150072D	Timer P/S 12V/24V DC <i>Timer P/S 12V/24V DC</i>																			
A1.02	150050	Supply/sensor cable 2P <i>Cablaggio 2P alimentazione/sensore</i>	1																		
A1.03	150056	Supply cable 5P+3P <i>Cablaggio 5P+3P alimentazione</i>	1																		
A1.04	150050	Supply/sensor cable 2P <i>Cablaggio 2P alimentazione/sensore</i>	1																		

**Table 02**



**Table 03**





Table	<b>02</b>	Parts list for 2 liter tank	Version	150102	150152	150202	150252	150302	150352	150402	150452	150502	150552	150602	150652
Group	<b>0</b>		Q	"Yellow" = present; "White" = missing											
Pos	Code	Description	Q												
02.01	150005	Policarbonate tank <i>Serbatoio policarbonato</i>	1												
02.02	150002	Screw M6x20 Dacromet <i>Vite M6x20 Dacromet</i>	4												

Table	<b>03</b>	Parts list 4÷8 liter tank for all version to 12/24V DC	Version	150104	150108	150154	150158	150204	150208	150254	150258	150304	150308	150354	150358
Group	<b>0</b>		Q	"Yellow" = present; "White" = missing											
Pos	Code	Description	Q												
03.01	120001	Increase tank flange <i>Flangia serbatoio maggiorato</i>	1												
03.02	120004	Screw M6 small head <i>Viti M6 testa piccola</i>	4												
03.03	120009	4÷8 liter tank brush windscreens <i>Paletta tergi vetro serbatoio 4÷8lt</i>	1												
03.04	120005	O-Ring 6670 <i>O-Ring 6670</i>	2												
03.05	120008	Policarbonate pipe for 4 liter tank <i>Tubo policarbonato serbatoio 4lt</i>	1												
	120502	Policarbonate pipe for 8 liter tank <i>Tubo policarbonato serbatoio 8lt</i>	1												
03.06	120007	Tie-rod M6 for 4 liter tank <i>Tirante M6 serbatoio 4lt</i>	4												
	120501	Tie-rod M6 for 8 liter tank <i>Tirante M6 serbatoio 8lt</i>	4												
03.07	120006	Increase tank cap <i>Tappo serbatoio maggiorato</i>	1												
03.08	120002	Nut M6 DIN 6923 <i>Dado M6 DIN 6923</i>	4												

Table	03	Parts list 4÷8 liter tank for all version to 110/220V AC	Q	Version	150404	150408	150454	150458	150504	150508	150554	150558	150604	150608	150654	150658
Group	1		Q	"Yellow" = present; "White" = missing												
Pos	Code	Description	Q	"Yellow" = present; "White" = missing												
03.01	120001	Increase tank flange <i>Flangia serbatoio maggiorato</i>	1													
03.02	120004	Screw M6 small head <i>Viti M6 testa piccola</i>	4													
03.03	120009	4÷8 liter tank brush windscreens <i>Paletta tergi vetro serbatoio 4÷8lt</i>	1													
03.04	120005	O-Ring 6670 <i>O-Ring 6670</i>	2													
03.05	120008	Policarbonate pipe for 4 liter tank <i>Tubo policarbonato serbatoio 4lt</i>	1													
	120502	Policarbonate pipe for 8 liter tank <i>Tubo policarbonato serbatoio 8lt</i>	1													
03.06	120007	Tie-rod M6 for 4 liter tank <i>Tirante M6 serbatoio 4lt</i>	4													
	120501	Tie-rod M6 for 8 liter tank <i>Tirante M6 serbatoio 8lt</i>	4													
03.07	120006	Increase tank cap <i>Tappo serbatoio maggiorato</i>	1													
03.08	120002	Nut M6 DIN 6923 <i>Dado M6 DIN 6923</i>	4													

TAB.	<b>O4</b>	Parts list pumping element and connection system	
SEZ.	<b>A</b>		
Pos	Code	Q	Description
04.01	092295	1	Pumping element with complet piston Ø6mm <i>Pompante con pistone Ø6mm completo</i>
04.02	094012	1	Washer 22,5x28x1,5 <i>Rosetta 22,5x28x1,5</i>
04.03	092294	1	Pumping element with piston Ø6mm <i>Pompante con pistone Ø6mm</i>
04.04	096014	1	Complete 90° fitting <i>Attacco a 90° completo</i>
04.05	093044	1	90° fitting G1/4" <i>Raccordo a 90° G1/4"</i>
04.06	093033	1	Lubricator A M6 UNI7663 <i>Ingrassatore A M6 UNI7663</i>
04.07	150010	1	Cap <i>Tappo</i>
04.---	092304	1	Complete signaling valve <i>Valvola di segnalazione completa</i>
04.08	023000	1	Signaling valve 250 bar <i>Valvola di segnalazione 250bar</i>
04.09	096028	1	3 way shunt G1/4" <i>Deviazione a 3 vie G1/4"</i>
04.---	092300	1	Complete Safety valve <i>Valvola di sicurezza completa</i>
04.---	100060	1	Safety valve 250 bar <i>Valvola di sicurezza 250bar</i>

Table 04






## PRODUCT ( Benefits)

### Centralized Lubrication Ciaponi ....

- ... lubrication even inaccessible points
- ... reduces wear
- ... reduces costs of repair and maintenances
- ... increases the duration of the media
- ... increases the availability of financial
- ... save the lubricant
- ... respects the environment
- ... it pays off in a short time




### Centralized Lubrication System Ciaponi ...

- ... save costs more than cost
- ... work in a completely automatic way
- ... they are robust and reliable
- ... do not fear the most difficult working conditions
- ... do not require virtually maintenance




Using the fat temperature variation



Fat distribution evenly on all surface



Cost reduction



To protect the environment

